

Xerox[®] VersaLink[®] C605 Color Multifunction Printer

VersaLink® C605 Color Multifunction Printers are built on Xerox® ConnectKey® Technology. For more information, go to www.ConnectKey.com.

System Specifications	VersaLink® 605	
One-sided Speed 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm	Up to 55 ppm color and black-and-white Up to 53 ppm color and black-and-white Up to 45 ppm color and black-and-white	
Two-sided Speed 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm	Up to 52 ppm color and black-and-white Up to 50 ppm color and black-and-white Up to 26 ppm color and black-and-white	
Monthly Duty Cycle ¹	Up to 120,000 pages / month ¹	
Recommended Average Monthly Print Volume ²	Up to 15,000 pages	
Hard Drive	320 GB HDD	
Processor	1.05 GHz	
Memory	4 GB	
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair	
Controller Features	Unified Address Book, Configuration Cloning, Scan Preview, Xerox Extensible Interface Platform®, Xerox App Gallery, Xerox® Standard Accounting, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled, Online Support	
User Interface Languages	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan, Ukrainian, Croatian	
Device Specifications		
Electrical Requirements		
North America	Voltage: 110-127V +/-10% Frequency: 50/60 Hz +/-3%, 12A	
Europe and Other Geographies	Voltage: 220-240V +/- 10 % Frequency: 50/60 Hz +/-3 % , 8A	
Power Consumption		
Continuous Printing ⁴	820 watts or less	
Ready (Standby) Mode ⁴	90 watts or less	
Energy Saver (Sleep) Mode ⁴	0.9 watts or less	
Operating Environment		
Required Temperature Range (Storage)	32° to 95° F (0° to 35° C)	
Required Temperature Range (Operating)	50° to 90° F (10° to 32° C)	
	15 % to 85 %	

Sound Power Levels Operating Standby	7.27 B(A) or less 4.84 B(A) or less			
Sound Pressure Levels Operating Standby	57.4 dB(A) or less 33.5 dB(A) or less			
Boot Time (from Off to UI Ready)	As fast as 65 seconds			
Warm-up Time (from Sleep to UI Ready)	As fast as 11 seconds			
Dimensions and Weight (Unpackaged)	Width	Depth	Height	Weight
Base Unit	18.5 in. / 470 mm	19.8 in. / 503 mm	25.4 in. / 643.7 mm	79.6 lb. / 36.1 kg
Base Unit with Mailbox	19.2 in. / 487.5 mm	19.8 in. / 503 mm	33.2 in. / 843.7 mm	97.2 lb. / 44.1 kg
Base Unit with Finisher	19.2 in. / 487.5 mm	19.8 in. / 503 mm	33.2 in. / 843.7 mm	100.5 lb. / 45.6 kg
Base Unit with High Capacity Feeder and Finisher	28.5 in. / 724.2 mm	30.4 in. / 772.1 mm	53.1 in. / 1302.7 mm	144 lb. / 65.3 kg
Base Unit with High Capacity Feeder and Mailbox	28.5 in. / 724.2 mm	30.4 in. / 772.1 mm	53.1 in. / 1302.7 mm	140.5 lb. / 63.8 kg
550-sheet Paper Tray	16.5 in. / 420 mm	18.3 in. / 464.5 mm	4.8 in. / 123 mm	4.1 lb. / 6.6 kg
High Capacity Feeder (includes Caster Base)	28.5 in. / 724.2 mm	30.4 in. / 772.1 mm	18.1 in. / 459 mm	43.4 lb. / 19.7 kg
Cabinet (includes Caster Base)	28.5 in. / 724.2 mm	30.4 in. / 772.1 mm	13.2 in. / 336 mm	37 lb. / 16.6 kg
Caster Base	28.5 in. / 724.2 mm	30.4 in. / 772.1 mm	3.5 in. / 90 mm	18.7 lb. / 8.5 kg
Mailbox	17.7 in. / 450.8 mm	18.8 in. / 477.6 mm	9.8 in. / 248.0 mm	11.7 lb. / 5.3 kg
Finisher	17.7 in. / 450.8 mm			15 lb. / 6.8 kg
Dimensions and Weight (Packaged)	Width	Depth	Height	Weight
Base Unit	23.4 in. / 594 mm	25.8 in. / 655 mm	31.1 in. / 789 mm	97 lb. / 44 kg
Base Unit with Mailbox	24 in. / 610 mm	26.4 in. / 670 mm	43.7 in. / 1110 mm	140.5 lb. / 63.8 kg
Base Unit with Finisher	24 in. / 610 mm	26.4 in. / 670 mm	43.7 in. / 1110 mm	142.8 lb. / 64.8 kg
Base Unit with High Capacity Feeder and Finisher	47.5 in. / 1206 mm	27 in. / 685 mm	51 in. / 1295 mm	271.6 lb. / 123.2 kg
Base Unit with High Capacity Feeder and Mailbox	47.5 in. / 1206 mm	27 in. / 685 mm	51 in. / 1295 mm	269.6 lb. / 122.3 kg
550-sheet Paper Tray	21.1 in. / 535 mm	23 in. / 584 mm	9.8 in. / 248 mm	18.7 lb. / 8.5 kg
High Capacity Feeder (includes Caster Base)	22.4 in. / 568 mm	26.1 in. / 663 mm	28 in. / 711 mm	83.8 lb. / 38 kg
Cabinet (includes Caster Base)	23 in. / 584 mm	24.8 in. / 629 mm	23.5 in. / 597 mm	57.3 lb. / 28 kg
Caster Base	23 in. / 585 mm	24.4 in. / 619 mm	13 in. / 330 mm	39.7 lb. / 18 kg
Mailbox	22.6 in. / 573 mm	20.4 in. / 518 mm	15.2 in. / 386 mm	16.3 lb. / 7.8 kg
Finisher	22.6 in. / 573 mm 15.7 in. / 398 mm 15.2 in. / 386 mm 18.6 lb. / 8.8 kg			
Certifications	ions			
	To view the latest list of certifications, go to www.xerox.com/OfficeCertifications.			
Print				
First-Print-Out Time	As fast as 10 seconds color and black-and-white			

Print Resolution	Up to 1200 x 2400 dpi	
Page Description Languages	PCL [®] 5e, 6 PDF XPS TIFF JPEG HP-GL Adobe [®] PostScript [®] 3 [™]	
Maximum Print Area	4 mm from edge of paper	
Print Features	Application Defaults Banner Pages Enable / Disable Bi-directional Real-time Status Booklet Layout Draft Mode Fit to New Paper Size Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Job Monitoring (Client or Local User Interface) LAN Fax (requires Fax Kit) N-up Page Layout (up to 16 pages per sheet) Paper Selection by Attribute Personal Print Print Around Enable / Disable Print from USB Sample Set Saved Job Scaling Secure Print Skip Blank Pages Special Pages (exception page programming: covers, inserts, exceptions pages) Store and Recall Driver Settings Stored Jobs Deletion Two-sided Printing (as default) Watermark (predefined and custom) Xerox® Earth Smart Driver Settings	
Print from USB	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A	
Operating Systems	Windows® 7, 8, 8.1, 10 Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016 macOS® 10.11, 10.12, 10.13 Citrix® Redhat® Enterprise Linux® Fedora Core IBM® AIX® HP-UX® Oracle® Solaris SUSE® SAP® Note: For information about supported versions for the above operating systems, please visit our	
Fonts	Drivers & Downloads page and specify your device at www.support.xerox.com. PostScript fonts: 136	
Xerox [®] Mobile Express Driver [®]	PCL fonts: 83 Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox® devices in every new location. Plug into a new network, and Mobile Express Driver® automatically discovers available printers and provides status and capability information. Save a list of "favorite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.	
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.	

Xerox [®] Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.	
Сору		
Document Scanner	100-sheet Single-Pass Duplex Automatic Document Feeder (DADF)	
Maximum Scan Area	Platen: Up to 8.5 x 14 in. / 216 x 356 mm DADF: Up to 8.5 x 14 in. / 216 x 356 mm	
Simplex Copy Speed	Up to 55 cpm (copies per minute) 8.5 x 11 in. Up to 53 cpm A4 / 210 x 297 mm	
Duplex Copy Speed	Up to 50 cpm (copies per minute) 8.5 x 11 in. Up to 47 cpm A4 (210 x 297 mm)	
First-Copy-Out Time	As fast as 7 seconds color / 5 seconds black-and-white	
Sides (input: output)	1:1, 1:2, 2:2 and 2:1	
Quantity	1 to 999	
Resolution (max.)	Up to 600 x 600 dpi	
Reduction / Enlargement	Variable zoom from 25% to 400% in 1% increments	
Concurrency	Concurrent scanning and printing	
Copy Features	Annotation (Page Numbers, Comments, Date Stamp, Bates Stamping)* Auto-color Sensing Automatic Background Suppression Book Copying with Center Erase Booklet Copying* Collation Color Balance Color Effects Darkness Control Edge Erase Front Cover ID Card Copy Image Enhancement Lighten / Darken N-up Reduce / Enlarge 25% to 400% Image Shift Original Orientation Original Size Original Type Page Layout Sample Copy Saturation Sharpness *Requires HDD / Productivity Kit	
Scan	Requires (1997) (Todated Vity Nic	
Capability	Black-and-white and color scanning	
Concurrency	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs	
Simplex Input Speed	Black-and-white: Scan up to 49 ipm 8.5 x 11 in. / 46 ipm A4 Color: Scan up to 47 ipm 8.5 x 11 in. / 46 ipm A4	
Duplex Input Speed	Black-and-white: Scan up to 75 ipm 8.5 x 11 in. / 71 ipm A4 Color: Scan up to 55 ipm 8.5 x 11 in. / 52 ipm A4	
Resolution	Optical – 600 x 600 dpi	

Bit Depth	24-bit color / 8-bit grayscale	
Maximum Scan Area	Platen: Up to 8.5 x 14 in. / 216 x 356 mm Document Feeder: Up to 8.5 x 14 in. / 216 x 356 mm	
Network Filing Protocols	FTP SMTP SMB	
File Formats	JPG TIFF (single and multi-page) XPS (single and multi-page) PDF (single and multi-page) Searchable PDF via Optical Character Recognition (OCR) Password-protected PDF Linearized PDF (set via embedded web server) and PDF/A	
Scan Driver Compatibility	WIA TWAIN	
Supported Scan Destinations	Scan to Home Scan to USB Scan to Email Scan to Network (Browse FTP or Browse SMB)	
Network Scanning – Software Sol	utions	
Xerox [®] ConnectKey [®] Apps (Found at the Xerox App Gallery)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey® Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey® Apps to the ConnectKey® Technology-enabled device.	
Fax ⁵		
Fax Speed	33.6 Kbps	
Memory	4 MB	
Resolution	Standard 200x100 dpi, Fine 200x200 dpi, Super Fine 300x300, 400x400, 600x600 dpi	
Compression	MH, MR, MMR, JBIG	
Fax Features	Walk-up Fax, LAN Fax, Direct Fax, Fax Forward to Email Fax dialing via Unified Address Book (up to 2,000 contacts)	
Mobile Solutions and Mobile Devi	ce Apps	
Apple [®] AirPrint [®]	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.	
Google Cloud Print™	Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook™ notebook computers and any other webconnected device.	
Mopriα [®] Certified	ConnectKey® Technology-enabled print devices are Mopria® certified. Mopria® certification ensures you can print wirelessly from your Mopria® supported (Android) smart phone, tablet and other mobile devices instantly and easily.	
@PrintByXerox	@PrintByXerox is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® printer or MFP using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address and release them at the MFP panel.	
Xerox [®] Print Service Plug-in for Android™ (Free at Google Play™ Store)	The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, web pages and documents when your mobile device is connected to printers or multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.	
Xerox [®] Mobile Link App (Free at Google Play™ Store and Apple [®] App Store)	The Xerox [®] Mobile Link App allows you to scan, email and fax from your phone or tablet by connecting with our multifunction printers and send data to and print data from cloud storage. It is easy to create Mobile Link One-Touch Workflows between a mobile device and a multifunction printer. Using a	

	manual address or QR code identification for pairing, automatic device discovery makes it easy to find and pair a mobile device with a nearby Xerox® multifunction printer.		
Xerox® Workplace Suite and Xerox® Workplace Cloud	Xerox [®] Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud based-version (Workplace Cloud) of this solution.		
Security			
Security Features	Access Controls AES 256-bit Encryption Audit Log Certificate Path Validation Certificate Revocation List (CRL) / Status Protocol (OCSP) Detection of External Program Falsification (XCP Plug-in) Cisco® Identity Services Engine (ISE) Integration Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite* IP Address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure Email Secure Fax Secure Print Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPv3 TLS / SSL		
Accounting	*Requires HDD / Productivity Kit		
Xerox® Standard Accounting / No	etwork Accounting (Standard)		
Tracking	Copy, Print, Fax, Scan and Email usage		
Accounting	Xerox® Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General Accounts Network Accounting (Job Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD Up to 14,000 Accounting Records (transactions)		
Features	Administrator can manage the feature via the Embedded Web Server.		
Accounting Options – Network A	ccounting (Allows central server to manage all accounting)		
	 Enhanced network accounting with up to the minute data on how the system is being used Comprehensive management and enterprise scale tracking and reporting of device usage Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com Security enhancements include simultaneous support for HTTP/HTTPS protocols Device requests account authentication from third party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third party Networking Account 		

Paper Handling			
Document Feeder	Document Feeder		
Capacity ³	Single-Pass Duplex Automatic Document Feeder (DADF): 100 sheets		
Sizes	Custom sizes: 5.5 x 5.5 in. to 8.5 x 14 in. / 140 x 140 mm to 216 x 356 mm		
Weights One-sided: Two-sided:	16 to 32 lb. bond / 60 to 128 gsm 16 to 32 lb. bond / 60 to 128 gsm		
Bypass Tray			
Capacity ³	150 sheets		
Sizes	Custom sizes: 3 x 5 in. to 8.5 x 14 in. / 76 x 127 mm to 216 x 356 mm		
Weights One-sided: Two-sided:	16 lb. bond to 80 lb. cover / 60 to 220 gsm 16 lb. bond to 65 lb. cover / 60 to 176 gsm		
Media Types	Bond Plain Paper Cardstock Custom Envelopes Hole Punched Labels Letterhead Lightweight Cardstock Pre-Printed Recycled		
Tray 1			
Capacity ³	550 sheets		
Sizes	Custom sizes: 3 x 7.5 in. to 8.5 x 14 in. / 76 x 190 mm to 216 x 356 mm		
Weights One-sided: Two-sided:	16 lb. bond to 80 lb. cover / 60 to 220 gsm 16 lb. bond to 65 lb. cover / 60 to 176 gsm		
Mediα Types	Bond Plain Paper Cardstock Custom Hole Punched Labels Letterhead Lightweight Cardstock Heavyweight Cardstock Pre-Printed Recycled Envelope		
Up to Four Additional Trays (Optional)			
Capacity ³	550 sheets		
Sizes	Custom sizes: 3 x 7.5 in. to 8.5 x 14 in. / 76 x 190 mm to 216 x 356 mm		
Weights One-sided: Two-sided:	16 lb. bond to 80 lb. cover / 60 to 220 gsm 16 lb. bond to 65 lb. cover / 60 to 176 gsm		

Media Types	Bond Plain Paper Cardstock Custom Hole Punched Labels Letterhead Lightweight Cardstock Heavyweight Cardstock Pre-Printed Recycled	
High Capacity Feeder (Only one a	dditional 550-sheet Tray can be added to High Capacity Feeder)	
Capacity ³	2,000 sheets	
Sizes	Letter / A4	
Weights One-sided: Two-sided:	16 lb. bond to 65 lb. cover / 60 to 176 gsm 16 lb. bond to 65 lb. cover / 60 to 176 gsm	
Media Types	Bond Plain Paper Hole Punched Letterhead Lightweight Cardstock Pre-Printed Recycled	
Total Capacity		
Standard Device Capacity ³	700 sheets	
Maximum Device Capacity ³	3,250 sheets	
Paper Output / Finishing		
Capacity ³	Up to 400 sheets	
Automatic Two-sided Printing	Standard	
Finisher		
Capacity ³	500-sheet tray, 50-sheet stapling	
Mailbox		
Capacity ³	Four 100-sheet bins	
Device Management		
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour [©] / AirPrint [™] FTP Most protocols not in use can be disabled	
Administrative Protocols	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS	

Xerox® CentreWare® Web Software			
	 A web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system Works with any SNMP-managed printer from any manufacturer Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management 		
Xerox® Embedded Web Server –	Integrated Device Web Page		
Device Status	 Tray Status / Contents Consumables Status Billing / Usage Quick Links Online Support 		
Print Queue Viewing	Job print queue management — view and delete		
Job Submission	Print-ready files (PS, PCL, PDF, XPS, JPEG)		
Device Administration	Allows simple, remote installation setting of configuration options and management of the device		
Browsers	Microsoft [®] Internet Explorer [®] Microsoft Edge [™] Mozilla [™] Firefox [®] Apple [®] Safari [®] Google Chrome [™]		
Remote Services			
Xerox® Automatic Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.		
Xerox [®] Automαtic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.		
What's In The Box			
	VersaLink® C605 Color Multifunction Printer Starter Capacity Print Cartridge: One of each (Cyan, Magenta, Yellow): 6,000 print capacity ⁶ , Black: 10,000 print capacity ⁶ Software and Documentation CD (Safety, Regulatory, Recycling and Disposal Guides, Print Drivers, and Warranty Statement) Installation Guide Quick Use Guides Power Cord Fax Cord		

Supplies and Accessories	Quantity	Part Number	
Supplies			
Standard Capacity Print Cartridges	Black: 6,000 standard pages ⁶ Cyan: 6,000 standard pages ⁶ Magenta: 6,000 standard pages ⁶ Yellow: 6,000 standard pages ⁶	106R03899 106R03896 106R03897 106R03898	
High Capacity Print Cartridges	Black: 12,200 standard pages ⁶ Cyan: 10,100 standard pages ⁶ Magenta: 10,100 standard pages ⁶ Yellow: 10,100 standard pages ⁶	106R03903 106R03900 106R03901 106R03902	
Extra-High Capacity Print Cartridges	Black: 16,900 standard pages ⁶ Cyan: 16,800 standard pages ⁶ Magenta: 16,800 standard pages ⁶ Yellow: 16,800 standard pages ⁶	106R03931 106R03928 106R03929 106R03930	
Routine Maintenance Items			
Drum Cartridges	Cyan: 40,000 pages ⁷ Magenta: 40,000 pages ⁷ Yellow: 40,000 pages ⁷ Black: 40,000 pages ⁷	108R01485 108R01486 108R01487 108R01488	
Waste Cartridge	30,000 pages ⁷	108R01416	
Accessories			
550-sheet Feeder		097S04949	
2,000-sheet High Capacity Feeder (includes Caster Base)		097S04948	
Cabinet (includes Caster Base)		097S04955	
Caster Base		097S04954	
Finisher (500 sheets, 50-sheet stapler)		097S04952	
4-Bin Mailbox (100 sheets per bin)		097S04953	
Wireless Network Adapter (Wi-Fi Kit)		497K16750	
Internal Card Reader / RFID Kit		497K18120	

 $^{^{1}}$ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program. For more information, visit www.xerox.com/About-Xerox/Recycling.

For more information, visit us at www.xerox.com/Office.

Configurations vary by geography.



Page 2 Expected regular monthly throughput.

Pager capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.

Requires analog phone line.

⁶Average standard pages. Declared Yield in accordance with ISO/IEC19798. Yield will vary based on image, area coverage and print mode.

⁷Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: https://www.office.xerox.com/Latest/SUPGL-01.pdf.