

Everything's Possible

Xerox® PrimeLink® C9265/C9275/C9281 Printer.



It's Time to Embrace Agility

When requests change by the minute, you need a printer that makes everything possible—luxury output, countless options for office and production-level feeding and finishing, with speedy, effortless workflows that help work get done faster. That's the all-new Xerox® PrimeLink® C9200 Printer Series.

NOW, ANYONE CAN PRINT LIKE A PRO

You'll do more with Xerox® PrimeLink®—a new light production engine that delivers more power with print speeds of up to 81 prints per minute. Whether you run an office, agency, university, or print production shop, Xerox® PrimeLink® is ready to enhance your image with seamless support and the broadest range of capabilities in the light production market.

LUXURY OUTPUT QUALITY

Image quality beyond what you'd expect from an office printer, with high-definition, highly engaging color output. Plus:

Crisp, rich black text and pristine, full-gamut color graphics with High Definition Emulsion Aggregate (HD EA) Toner

Optimized 0.5 mm front-to-back registration to keep all your content exactly where you want it

More stable and accurate quality with new energy-efficient LED print technology, providing 2400 x 2400 dpi imaging

Accurate density and color quality with advanced Simple Image Quality Adjustment (SIQA)

Support for expanded Extra-long Sheet (XLS) printing at greater sizes (51 in./1,300 mm)

Reliable envelope feeding in a wide array of sizes comes standard—no special kit required



WIDE RANGE OF FEEDING AND FINISHING

Effortless production of any run—small to large—with inline finishing on virtually any media ensures you're set up for success.

- **Offer more applications** with greater media flexibility, up to 400 gsm, and sizes up to 51 in./1,300 mm
- **Optimize your printer for every job** with Custom Stock Libraries
- **Get big capability and productivity** in a space-saving footprint

A PRINTER SO FUN TO USE, WORK WON'T FEEL LIKE WORK

When it comes to working better, it's all about efficiency and excellence. The new Integrated Color Server for the Xerox® PrimeLink® C9200 Printer Series delivers that and more (standard) with ready-to-use workflows and advanced print features, accessed via a 10-inch touchscreen for tap-and-print/copy/scan convenience.

The Xerox® EX and EX-i C9200 Series Print Servers Powered by Fiery® (optional) offer production tools familiar to print shops and in-printers—including a wide range of Fiery® offerings for advanced color management, job set-up, and more.

SPEEDY, EFFORTLESS WORKFLOWS AND CUSTOMIZATION

Time- and talent-saving automation with the potential to transform your workflows—and your working environment.

- **Accelerate your work** with Xerox® FreeFlow® Core and other FreeFlow® Workflow Software solutions
- **Monitor, measure, and manage** your printer or entire fleet with Xerox® FreeFlow® Vision Software
- **Connect and create** with the Xerox® Connect App for XMPie for creative new applications, including preloaded templates for personalization
- **Seamlessly print from any device** with support for mobile printing via the Xerox® @PrintByXerox App

SUPER-SECURE FROM TODAY'S—AND TOMORROW'S—THREATS

With dozens of security features and certifications, Xerox® PrimeLink® is ready to meet and exceed your organization's protocols. Our multi-layered approach to security is designed around three principles to ensure ongoing protection and compliance—whatever your field or industry.



The All-new, From-the-ground-up Xerox® PrimeLink® C9200 Printer Series



Shown: Fiery® EX Print Server, Two-tray Oversized High Capacity Feeder, Xerox® PrimeLink® C9200 Printer Series, Xerox® Crease Two-sided Trimmer, Xerox® Production Ready Booklet Maker Finisher, Xerox® SquareFold® Trimmer



Speeds:
65/75/81 ppm



Media weights:
Up to 400 gsm




Banner media:
Up to 51 in./1,300 mm



Standard (5-tray) capacity:
3,500 sheets (with optional
One-tray Oversized High
Capacity Feeder [OHCF])
7,500 sheets
(with Two-tray OHCF)

- 1 Optional one- or two-tray Oversized High Capacity Feeders (OHCF)
- 2 Tray 5 (Multi-sheet Inserter (MSI)/Bypass tray)
- 3 Remote user interface
- 4 Smart proximity sensor
- 5 Dual-head color scanner up to 270 ipm
- 6 Standard trays 1-5
- 7 Optional Xerox® EX or EX-i C9200 Series Print Servers Powered by Fiery®
- 8 Standard Integrated Color Server for the Xerox® PrimeLink® C9200 Printer Series

- 9 High Definition Emulsion Aggregate (HD EA) toner
- 10 LED print technology
- 11 Intelligent/Advanced decurler
- 12 Registration: 0.5 mm front-to-back
- 13 Custom stock library
- 14 Redesigned paper path
- 15 Xerox® Crease Two-sided Trimmer
- 16 Xerox® SquareFold® Trimmer
Multiple finishing options for production print and office environments



We make it easy
to make it yours.
Auto-configure
your ideal press
with our Product
Explorer tool.



Xerox® PrimeLink® C9265/C9275/C9281 Printers

DEVICE SPECIFICATIONS		PRIMELINK C9265		PRIMELINK C9275		PRIMELINK C9281	
SIMPLEX SPEEDS		Color	Black-and-white	Color	Black-and-white	Color	Black-and-white
8.5 x 11 in./A4		Up to 65 ppm	Up to 65 ppm	Up to 75 ppm	Up to 75 ppm	Up to 81 ppm	Up to 81 ppm
11 x 17 in./A3		Up to 34 ppm	Up to 34 ppm	Up to 37 ppm	Up to 37 ppm	Up to 42 ppm	Up to 42 ppm
12 x 18 in./SRA3		Up to 30 ppm	Up to 30 ppm	Up to 34 ppm	Up to 34 ppm	Up to 38 ppm	Up to 38 ppm
Printer Dimensions		Height: 45.4 in./1,154 mm; Width: 62 in./1,575 mm; Depth: 31.2 in./793 mm (includes Bypass Tray and Offset Catch Tray)					
Monthly Duty Cycle		Up to 300,000 pages (maximum volume capacity expected in any one month, not intended to be sustained regularly)					
Average Monthly Print Volume (AMPV)		10,000 to 60,000 pages per month					
Paper Flexibility/Weights		Standard Paper Capacity: 3,500 sheets: (Tray 1 and 2: 540 sheets, Tray 3: 890 sheets, Tray 4: 1,280 sheets, Tray 5 (MSI/Bypass): 250 sheets) Maximum Paper Capacity: 7,500 sheets (Tray 1 and 2: 540 sheets, Tray 3: 890 sheets, Tray 4: 1,280 sheets, Tray 5 (MSI/Bypass): 250 sheets, Two-tray Oversized High Capacity Feeder: 4,000 sheets) Sizes: Tray 1: 3.93 x 5.82 in. (100 x 148 mm) to 13 x 19.2 in. (330.2 x 488 mm); Tray 2: 3.93 x 5.82 in. (100 x 148 mm) to 13 x 19.2 in. (330.2 x 488 mm); Tray 3: 7.25 x 10.5 in. (184 x 267 mm) to 8.5 x 11 in./A4; Tray 4: 7.25 x 10.5 in. (184 x 267 mm) to 8.5 x 11 in./A4					
Image Quality	Print Technology	Setting a new, higher benchmark for light production image quality with LED technology, the printer delivers 2400 x 2400 dpi resolution using advanced HD LED and HD EA Toner for exceptional clarity and vibrant, rich colors					
	Line Screens	It supports 150/200/300/600 dot screens, a 200-line screen, stochastic screening, and enhanced text and graphics					
	Registration	- Cutting-edge registration technology for tight control - Simple Image Quality Adjustment (SIQA) for de-skew, registration, and density uniformity (available on all configurations) +/- 0.5 mm; variation may occur based on paper size, tray, etc.					
Print Features		- Print, copy, scan, and fax (optional), including scan to PC, USB, or email, and mobile printing - The expansive media range allows you to print everything from postcards to posters, on both coated and uncoated stock, up to 400 gsm - The Xerox Extensible Interface Platform® (EIP) enables connectivity with third-party software solutions - Inline finishing options provide a professional polish, including banner printing, stapling, hole punching, folding, booklet stitching, creasing, and three-knife trimming—for booklets, stitched presentations, reports, and newsletters - Stay secure with integrated security features such as Internet Protocol (IP) filtering, image overwrite, secure print, encrypted scan to email, authentication, and IPv6 support 51 in./1,300 mm XLS or Banner sheet size (Tray 5) supporting up to 220 gsm 26 in./660 mm XLS or Banner sheets in Tray 5 with OHCF up to 220 gsm - Up to 400 gsm media weight (Tray 5 and Two-tray OHCF only), with auto-duplex printing up to 350 gsm (Bypass Tray and OHCF) - Xerox® replaceable units for toners, drums, fuser, charge corotron, waste bottles, staples - Custom Paper Setup and Paper Catalog - Load-while-run toner and paper capability - Remote UI and Smart Proximity Sensor - Optional Features: Common Access Card Enablement Kit, Accounting Options, PostScript with Integrated Color Server					
Servers		- Integrated Color Server for the Xerox® PrimeLink® C9200 Series (Must be ordered separately in some geographies) - Xerox® EX-i C9200 Series Print Server Powered by Fiery® (FS600 Platform) (Optional) - Xerox® EX C9200 Series Print Server Power by Fiery® (FS600 Platform) (Optional)					
Integrated Scanner		- Single-pass Automatic Duplex Document Feeder - Color or black-and-white scanner - Thumbnail preview, XPS, TIFF, JPEG, Scan to searchable text PDF (Optional), PDF/A 250-sheet capacity - Up to 270 ipm (color, up to 200 gsm) - Up to 270 ipm (black-and-white, up to 200 gsm) - Originals up to 11 x 17 in./A3 in weights from 38 gsm/16 lb. bond to 200 gsm/53 lb. bond - Auto Document Feeder and platen glass used with SIQA (Tray to Paper registration)					
Optional Feeding		Optional High Capacity Feeder (HCF): 2,000 sheets; 7.25 x 10.5 in., 8.5 x 11 in./184.2 x 266.7 mm, 279.4 x 215.9 mm/ B5, A4; 16 lb. bond to 60 lb. cover/60 to 220 gsm (uncoated and coated) Optional Oversized High Capacity Feeder (OHCF): One-Tray OHCF: o Capacity: 2,000 sheets + storage cabinet, Tray 6 – 3.9 x 5.8 in./100 x 148 mm to 13 x 19.2 in./330 x 488 mm (60 to 350 gsm) Two-Tray OHCF: o Capacity: 4,000 sheetso Tray 6 and 7 – 3.9 x 5.8 in./100 x 148 mm to 13 x 19.2 in./330 x 488 mm (60 to 400 gsm) OHCF Tray 5/bypass tray: Maximum banner sheet (XLS) is 13x 26 in./330 x 660 mm/220 gsm					
Optional Finishing		Business Ready Finisher 2.0: Offsetting Top Tray: 500 sheets 8.5 x 11 in./A4, unstapled. Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position staple) 11 x 17 in., 8.5 x 14 in., A3 or 200 sets (single-position staple) 8.5 x 11 in./A4. Sizes: Stacking: 4 x 6 in. to 13 x 19.2 in./A6 to SRA3. Stapling: 7.25 x 10.5 in. to 11 x 17 in./B5 to A3. Other: 5.5 x 8.5 in./A5 output to top tray; punch and offset. Paper weights: Top Tray: 16 lb. bond to 110 lb. cover/60 to 350 gsm (coated and uncoated). Stacker Tray: 16 lb. bond to 96 lb. cover/60 to 256 gsm (coated and uncoated). Business Ready Finisher Booklet Maker Finisher 2.0: Offsetting Top Tray: 500 sheets 8.5 x 11 in./A4 unstapled. Stacking Stapling Tray: 1,500 sheets unstapled or 200 sets (single position stapling or dual or 4-position staple) or 100 stapled sets of 11 x 17 in./A3/SRA3. 11x17 in., 8.5 x 14 in., A3 or 200 sets (single-position staple) 8.5 x 11 in./A4. Sizes: Stacking: 4 x 6 in. to 13 x 19.2 in./A6 to SRA3. Stapling: 7.25 x 10.5 in. to 11 x 17 in./B5 to A3. Other: 5.5 x 8.5 in. /A5 output to top tray; punch and offset. Paper weights: Top Tray: 16 lb. bond to 130 lb. cover/60 to 350 gsm (coated and uncoated), Stacker Tray: 16 lb. bond to 96 lb. cover/60 to 350 gsm (coated and uncoated). Booklet Maker: 16 lb. bond to 110 lb. cover/256 to 300 gsm cover (uncoated, 106 to 220 gsm (coated)). Booklet Maker/Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 177 to 220 gsm coated). Xerox® Production Ready Finisher (requires Interface Decurler Module): Booklet Size: 100 sheets (90 gsm) uncoated, 35 sheets (90 gsm) coated. Paper Size: 7.2 x 5.7 in./182 in. x 146 mm to 11.7 x 17 in./297 x 432 mm. Maximum Weight: 350 gsm. Options: Punch, Inserter, and C/Z Folder. Trays: Two output trays, 500-sheet top tray, 3,000-sheet stack tray of 5.83 x 5.75 in./148 x 146 mm to 13 x 19.2 in./330 x 488 mm. Xerox® Production Ready Booklet Maker Finisher (requires Interface Decurler Module): Booklet Size: 7.17 x 7.17 in./182 x 182 mm to 13 x 19.2 in./330 x 488 mm up to 256 gsm. Trays: 500-sheet top tray, 2,000-sheet stack tray, saddle-stitch booklet tray (up to 120 pages, 30 sheets/90 gsm uncoated, 15 sheets/106 gsm coated). Offset Catch Tray: 500 sheet stacking. Xerox® SquareFold® Trimmer Module: Face Trim: 120 pages (30 sheets). Compatibility: Xerox® Production Ready Finisher, Xerox® Production Ready Booklet Maker Finisher, and Xerox® Crease and Two-Sided Trimmer. Xerox® C/Z Folder: Sheet Size: 8.5 x 11 in./A4. Half Z-fold Sheet Size: Larger stocks reducing to 8.5 x 11 in./A4. Weight Range: 64 to 90 gsm. Compatibility: Xerox® Production Ready Booklet Maker Finisher. Xerox® Inserter: Capacity: 250 sheets. Capabilities: Trimming, punching, folding, stapling, and stacking. Paper Size: 7.2 x 5.8 in./182 x 148 mm to 13 x 19.2 in./330 x 488 mm. Maximum Weight: 350 gsm. Compatibility: Xerox® Production Ready Finisher. Xerox® Crease Two-sided Trimmer: Trim Range: 0.236 in./6 mm to 0.985 in./25 mm. Paper Size: 7.7 x 8.3 in./194 x 210 mm to 13 x 19.2 in./330 x 488 mm. Maximum Weight: 350 gsm. Compatibility: Xerox® Production Ready Booklet Maker Finisher. Buffering Unit: Up to five customizable mountain or valley creases per sheet. For more optional finishing, refer to the Product Explorer at explore.xeroxproducts.com/Product.					
Xerox App Gallery		Visit xerox.com/AppGallery to learn how you can expand the capabilities of the Xerox® PrimeLink® C9265/C9275/C9281 Printer Series and work in new ways with dedicated apps for business, education, healthcare, and more.					

Configurations may vary by geographical location.

For more information, visit xerox.com